

JSD20-10M1/JSD24-12M1/JSD32-16M1



Introduction:

Product name: Instantaneous gas fired water heater Product types: JSD20-10M1, JSD24-12M1, JSD32-16M1

Feature and benefits:

- 1. Full automatic water control and large hot water supply.
- 2. Low start-up water pressure and digital display of water temperature.
- 3. Flue venting water heater is with multiple safety protections.
- 4. Simple and refined European design.

Advantages:

1. Auto ignition. Hot water comes out by turning on inlet valve.

- 2. Hot water stops running and fire extinguishes immediately by turning off the water valve.
- 3. Water flow and heat power are controlled separately.
- 4. Combustor and heat exchanger are with innovative design, good combustion performance, high thermal efficiency and low energy consumption.
- 5. Our gas fired water heater is CE certified.

6. Installed with high sensitive IC ion flame device, which can cut off inner power of water heater immediately in accidental flameout.

7. Automatic shutdown every 20 minutes.

- 8. Start under low water pressure to meet requirements of users in high-rise buildings.
- 9. It is with heat power adjustment in section, which makes temperature adjustment easier.

10. It is equipped with device that makes water temperature be in consistent with seasons. It can supply water with different temperature in four seasons.

Specification:

Туре	JSD20-10M1	JSD24-12M1	JSD32-16M1
Rated heat load (kW)	20	24	32
Rated capability of hot water supply $(\triangle T=25^{\circ}C)$	10kg/min	12kg/min	16kg/min
Rated gas pressure	Liquefied petroleum gas 2800 pa		



Guangdong Vanward New Electric CO., LTD

	Natural gas 2000 pa			
	Manufactured gas 1000 pa			
Control method	By outlet valve			
Exhaust method	Flue type			
Applicable water pressure (Mpa)	0.02-1.0			
Gas entrance	G1/2 or G3/4			
Cold water inlet	G1/2			
Hot water outlet	G1/2			
Product size (mm)	636×350×225	636×350×225	680×410×223	
Package size (mm)	735×405×300	735×405×300	780×468×300	
Gross weight/net weight (kg)	12.8/11.3	13.3/11.8	18.3/15.1	
Container number 20'/40'/40'HQ	320/660/768	320/660/768	250/530/620	

Flue Venting Water Heater in Vanward

JSD20-10M1/JSD24-12M1/JSD32-16M1	JSD20-10P1/JSD24-12P1/JSD32-16P1
JSD12-6CL/JSD14-7CL/JSD16-8CL/JSD20	JSD12-6CR/JSD14-7CR/JSD16-8CR/JSD20-10CR
-10CL	
JSD12-6CA/JSD14-7CA/JSD16-8CA	JSD12-6CC/JSD14-7CC/JSD16-8CC