

# JSQ20-10G36/JSQ24-12G36/JSQ32-16G36



### Introduction

Name: Instantaneous hot water heater Type: JSQ20-10G36, JSQ24-12G36, JSQ32-16G36

## Feature and benefits:

1. Constant temperature gas water heater is with multiple intelligent gas supply and wide-range water temperature adjustment

2. Second generation of six high-effective and energy saving combustion technology and condensing heat exchange technology with highest heat efficiency reaching to 103%

3. Wireless remote control technology

4. Multi-functional LED display and touch monitor

5. Multiple safety protections and automatic fault detecting code

### Advantages:

- 1. Patent of integrated stainless steel condensation technology
- 2. Instantaneous hot water heater adopts second generation of AI intelligent constant engine
- 3. DC electrodeless frequency conversion combustion technology
- 4. Special water flow server (water and gas adjustment)
- 5. New three valve and five speed intelligent section combustion technology.
- 6. Precise magnetic levitation type gas proportional valve.
- 7. Z-type combustor with stable flame core.
- 8. Forced combustion technology with full seal.
- 9. Water flow sensor with high precision.
- 10. Oxygen-free copper water bank with high efficiency and environment friendly.

Туре	JSQ20-10G36	JSQ24-12G36	JSQ32-16G36
Rated heat load (kW)	20	24	32
Rated capability of hot water supply ( $\triangle T=25^{\circ}C$ )	10kg/min	12kg/min	16kg/min
Rated gas pressure	Liquefied petroleum gas 2800 pa		
	Natural gas 2000 pa		

#### Specifications of constant temperature gas water heater:



# Guangdong Vanward New Electric CO., LTD

	Manufactured gas 1000 pa			
Control method	By outlet valve			
Exhaust method	Forced type			
Applicable water pressure (Mpa)	0.02~1.0			
Gas entrance	G1/2 or G3/4			
Cold water inlet	G1/2			
Hot water outlet	G1/2			
Product size (mm)	Ф60	Ф60	Ф80	
Control method	550×360×138	550×360×138	550×360×138	
Package size (mm)	740×490×220	740×490×220	740×490×220	
Gross weight/net weight (kg)	16/14	16/14	18/16	
Container number 20'/40'/40'HQ	350/720/850	350/720/850	350/720/850	